

Multi-Pads

Paving Slab Corner Support Pads

Description

Specifically designed corner supports for precast concrete paving slabs, glass reinforced concrete or compressed fibre cement panels, etc. Chemind Multi-Pads are engineered from high quality exterior grade polypropylene.

Uses

Used in combination with suitable paving slabs, Chemind Multi-Pads provide a fully trafficable surface to roofs, balconies, decks and podiums.

Provides functional protection of Chemind and Grace waterproof membrane systems.

Used as trafficable surfacing over Chemind Insul-Foam for exposed insulated roof membrane.

Multi-Pads provide access to roof membrane when required, by easy removal of modular surfacing system.

Features

- The paved area is self-draining
- Resistant to oils, acids and alkalis
- Will not react adversely with membrane
- Compatible with all Chemind and Grace waterproof membrane systems
- Services may be concealed but still remain accessible
- Facilitates easy maintenance or repair of roof waterproof membrane system
- Creates air space under paving reducing heat and noise transmission to structural slab
- Paving can be laid on concrete slabs to fall, or can be laid level through the use of packers or bedding



Dimensions

Base Diameter	120 mm
Base Thickness	3 mm
Vertical Spacer Height	19 mm
Spacer Width	3 mm

Application

Multi-Pads should be installed in accordance with the architectural drawing and good building practice.

Pre-cast concrete paving slabs are generally 600 x 600 x 40-50 mm thickness.

Cut and fit Multi-Pads and concrete paving slabs to suit roof plan. Washed river stone roofing ballast may be used in conjunction as infill to partitions and parapets.

Multi-Pads may be elevated by the use of a rigid packing shim, dry-pack mortar bedding or supported on granulated rubber blocks.

NOTE

Particular design requirements for Multi-Pads used in conjunction with Chemind waterproofing membrane systems or Insul-Foam closed cell roof insulation (IRMA) should be referred to the Chemind Technical Department.

Coverage

Coverage will vary according to slab size. Generally allow 1.5 Multi-Pads per paving slab.

Additional pads may be required if narrow or geometrically designed paving is required.



HEAD OFFICE
74 Annie Street
ROCKLEA QLD 4106
AUSTRALIA
Ph: (+617) 3255 5755
Fax: (+617) 3255 5991
ABN: 63 250 804 992